


**Capacitive Sensors
Series 95 - AC / DC**

Housing M 30 x 1.5


- Housing material POM
- Sensing distance 2...20 mm adjustable
- Normally open and normally closed function
- One potential-free change-over contact
- Switch-off delay adjustable 1 sec. - 10 min.

Certificate:



Technical data	Non-flush mountable
Operating distance S_n	15 mm
Operating distance min./max. adjustable	2...20 mm
Electrical version	5-wire AC / DC
Output	Relay, 1 CO
Type	KAS-95-A24-1CO-K-POM-OFD
Art.-No.	KA 0750
Operating voltage (U_b)	20...250 AC / DC
Load max. AC (I, U)	1 A, 250 V
Load max. DC (I, U, P)	1 A, 220 V, 60 W
No-load current (I_o)	2,1 mA
Frequency of operating cycles max.	2 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-In
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	2 m, PVC, 5 x 0,34 mm ²
Housing material	POM
Active surface	POM
Lid	POM

*With sealed potentiometer


Made in Germany

All specifications are subject to change without notice. (25.03.2009)